



Unidades Condensadoras

Compact Line - Alta y media temperatura de evaporación

Modelo	Volt/F/Hz	Potencia H.P.	Peso (Kg)	Ventilador		Recibidor de líquido (Lts.)	Conexiones		Dimensiones			Código Antartic
				Caudal (m ³ /h)	Diam. (mm)		Succión	Líquido	A (mm)	B (mm)	C (mm)	
HAM 010	220/1/50	1,0	40	1.400	1x300	3,1	1/2"	3/8"	610	450	345	1250DA-300
HCM 012	220/1/50	1,0	35	1.400	1X300	1,7	3/8"	3/8"	430	550	370	1250DA-105
HCM 018	220/1/50	1,5	45	1.400	1x300	3,1	1/2"	3/8"	700	500	442	1250DA-111
HCM 018	380/3/50	1,5	45	1.400	1x300	3,1	1/2"	3/8"	700	500	442	1250DA-110
HCM 022	220/1/50	2,0	54	2.325	1x350	3,1	1/2"	3/8"	700	500	442	1250DA-115
HCM 022	380/3/50	2,0	54	2.325	1x350	3,1	1/2"	3/8"	700	500	442	1250DA-112
HCM 028	220/1/50	2,5	61	4.100	1x450	6,0	5/8"	1/2"	800	600	548	1250DA-113
HCM 028	380/3/50	2,5	61	4.100	1x450	6,0	5/8"	1/2"	800	600	548	1250DA-114
HCM 036	380/3/50	3,0	70	4.100	1x450	7,5	5/8"	1/2"	800	700	696	1250DA-118
HCM 040	380/3/50	3,5	81	4.100	1x450	7,5	5/8"	1/2"	800	700	696	1250DA-120
HCM 050	380/3/50	4,5	91	4.100	1x450	7,5	7/8"	1/2"	800	700	696	1250DA-122

Compact Line - Baja temperatura de evaporación

Modelo	Volt/F/Hz	Potencia H.P.	Peso (Kg)	Ventilador		Recibidor de líquido (Lts.)	Conexiones		Dimensiones			Código Antartic
				Caudal (m ³ /h)	Diam. (mm)		Succión	Líquido	A (mm)	B (mm)	C (mm)	
LCZ 048	220/1/50	1,8	46	1.400	1x300	3,1	1/2"	3/8"	700	500	442	1250DA-208
LCZ 068	220/1/50	2,3	56	2.325	1x350	3,1	5/8"	3/8"	700	500	442	1250DA-215
LCZ 022	380/3/50	1,8	46	1.400	1x300	3,1	1/2"	3/8"	700	500	442	1250DA-200
LCZ 028	380/3/50	2,3	56	2.325	1x350	3,1	5/8"	3/8"	700	500	442	1250DA-202
LCZ 040	380/3/50	3,3	63	4.100	1x450	7,5	7/8"	1/2"	800	700	696	1250DA-205
LCZ 044	380/3/50	3,6	72	4.100	1x450	7,5	7/8"	1/2"	800	700	696	1250DA-121
LCZ 050	380/3/50	4,2	83	4.100	1x450	7,5	7/8"	1/2"	800	700	696	1250DA-210

Blue Star - Alta y media temperatura de evaporación

Modelo	Volt/F/Hz	Potencia H.P.	Peso (Kg)	Ventilador		Recibidor de líquido (Lts.)	Conexiones		Dimensiones			Código Antartic
				Caudal (m ³ /h)	Diam. (mm)		Succión	Líquido	A (mm)	B (mm)	C (mm)	
HGM 064	380/3/50	5,3	115	9.000	2X450	10	7/8"	1/2"	1200	800	671	1250DA-125
HGM 080	380/3/50	6,7	124	8.600	2X450	10	1-1/8"	1/2"	1200	800	671	1250DA-130
HGZ 080	380/3/50	6	124	8.600	2X450	4,5	1-1/8"	1/2"	1200	800	671	1250DA-133
HGM 100	380/3/50	8,3	154	8.000	2X450	14	1-1/8"	5/8"	1200	800	671	1250DA-140
HGM 125	380/3/50	10,4	225	14.000	2X600	14	1-1/8"	5/8"	1500	870	975	1250DA-145
HGM 160	380/3/50	13,6	245	12.500	2X600	14	1-1/8"	5/8"	1500	870	975	1250DA-148

Blue Star - Baja temperatura de evaporación

Modelo	Volt/F/Hz	Potencia H.P.	Peso (Kg)	Ventilador		Recibidor de líquido (Lts.)	Conexiones		Dimensiones			Código Antartic
				Caudal (m ³ /h)	Diam. (mm)		Succión	Líquido	A (mm)	B (mm)	C (mm)	
LGZ 088	380/3/50	7,3	144	9.000	2X450	10	1/18"	1/2"	1200	800	671	1250DA-220
LGZ 100	380/3/50	8,3	150	9.000	2X450	10	1/18"	1/2"	1200	800	671	1250DA-230