



Evaporadores Características y rendimientos

Características y capacidades

Modelo	Motoventilador con hélice de 254 mm				Resistencia eléctrica *		Dimensiones Largo A mm	Diámetro Descarga Ø
	N° de motores	Caudal de aire m ³ /h	Potencia Watts	220 V Amperes	Potencia Watts	220 V Amperes		
4 mm LAE 078	2	1.802	146	1,2	900	8,2	1.041	1/2"
LAE 109	2	1.716	146	1,2	900	8,2	1.041	5/8"
LAE 132	2	1.607	146	1,2	900	8,2	1.041	7/8"
LAE 175	3	2.574	219	1,8	1.350	12,3	1.404	7/8"
LAE 193	3	2.410	219	1,8	1.350	12,3	1.404	1-1/8"
LAE 234	4	3.432	292	1,8	1.800	16,4	1.767	7/8"
LAE 254	4	3.215	292	2,4	1.800	16,4	1.767	1-1/8"
LAE 294	5	4.290	365	2,4	1.800	16,4	2.130	1-1/8"
6 mm LBE 066	2	1.858	146	1,2	900	8,2	1.041	1/2"
LBE 092	2	1.769	146	1,2	900	8,2	1.041	5/8"
LBE 113	2	1.657	146	1,2	900	8,2	1.041	7/8"
LBE 150	3	2.654	219	1,8	1.350	12,3	1.404	7/8"
LBE 168	3	2.485	219	1,8	1.350	12,3	1.404	1-1/8"
LBE 196	4	3.538	292	1,8	1.800	16,4	1.767	7/8"
LBE 217	4	3.314	292	2,4	1.800	16,4	1.767	1-1/8"
LBE 252	5	4.423	365	2,4	1.800	16,4	2.130	1-1/8"

(*) Todos los modelos con 2 resistencias eléctricas

Rendimientos

4 mm

Modelo	TEMPERATURA DE EVAPORACIÓN °C										
	-40	-35	-30	-25	-20	-15	-10	-5	0	5	10
LAE 078	1.610	1.673	1.738	1.805	1.863	1.911	1.945	2.030	2.164	2.278	2.383
LAE 109	2.235	2.322	2.412	2.496	2.579	2.658	2.706	2.825	3.014	3.181	3.335
LAE 132	2.730	2.836	2.946	3.051	3.157	3.238	3.293	3.443	3.664	3.872	4.081
LAE 175	3.612	3.753	3.899	4.028	4.156	4.262	4.358	4.568	4.860	5.140	5.421
LAE 193	3.977	4.133	4.293	4.441	4.578	4.704	4.822	5.050	5.370	5.667	5.964
LAE 234	4.831	5.220	5.214	5.379	5.556	5.697	5.823	6.093	6.492	6.856	7.220
LAE 254	5.228	5.432	5.642	5.825	6.018	6.167	6.313	6.644	7.042	7.441	7.840
LAE 294	5.846	6.075	5.310	6.520	6.741	6.905	7.068	7.593	8.176	8.620	9.063

6 mm

Modelo	TEMPERATURA DE EVAPORACIÓN °C										
	-40	-35	-30	-25	-20	-15	-10	-5	0	5	10
LBE 066	1.344	1.401	1.468	1.516	1.563	1.611	1.640	1.716	1.830	1.926	2.011
LBE 092	1.899	1.970	2.053	2.124	2.207	2.255	2.302	2.421	2.575	2.706	2.848
LBE 113	2.327	2.409	2.501	2.582	2.683	2.759	2.806	2.945	3.130	3.304	3.478
LBE 150	3.096	3.201	3.318	3.423	3.540	3.633	3.715	3.902	4.147	4.393	4.626
LBE 168	3.464	3.606	3.738	3.782	3.988	4.102	4.205	4.299	4.685	4.936	5.199
LBE 196	4.027	4.191	4.356	4.496	4.637	4.766	4.872	5.107	5.447	5.741	6.034
LBE 217	4.467	4.649	4.820	4.980	5.139	5.276	5.401	5.664	6.017	5.359	6.701
LBE 252	5.004	5.202	5.389	5.575	5.750	5.902	6.042	6.485	6.987	7.372	7.756